

NS-3703

全蒸汽熨鬥(手按式)

Steam Heated Iron (Press Handle Type)



- 最適用於邊縫開骨工序
- 底板與蒸汽室一體結構，升溫迅速
- 采用蒸汽循環加熱方式，實現在低溫下熨燙操作
- 特別設計之狹長底板及光滑的尖頭，有助於熨斗導向正確位置，使分縫熨燙工序簡單易行，並且狹長底板更能節約能源
- 手按式高性能蒸汽閥，輕松、靈活控制蒸汽發生

選購件：

C28-010-06-1 熨鬥鞋(讓您遠離布料因對溫度敏感而產生鏡面現象的煩惱)

C18-S-02-2E 疏水閥

- Best for side seam opening
- Iron sole and steam chamber are as a whole, temperature rising quickly
- Apply steam circulation heating mode, it could be operated in low temperature
- Specially designed long and narrow iron sole, and smooth sharp head, which is helpful for the iron to the correct position and makes it easy and simple for seam opening and ironing, especially, a long and narrow sole could save energy
- Swing handle type steam valve for adjusting steam volume flexibly


Options:

C28-010-06-1 Special designed Teflon shoe (Its thermal insulation helps you get rid of the annoyance caused by heat sensitive fabric)
C18-S-02-2E Steam trap



1. 獨特手柄設計，操作舒適
2. 采用蒸汽循環加熱方式，實現低溫熨燙都不會漏水
3. 底盤設計獨特，最適合邊縫開骨

1. Specially designed handle for comfortable operation
2. Apply steam circulation heating mode, there is no water leakage even when ironing in lower temperature
3. Specially designed iron sole is best for seam opening



熨鬥尺寸簡圖
Iron Dimensions Diagram (mm)

選購件 Options



C18-S-02-2E
疏水閥(1/4")
Steam Trap(1/4")

C28-010-06-1
熨鬥鞋
Teflon Shoe

C31-CES-10-33M
吊熨鬥彈簧
Iron Hanging Spring

跟機件 Delivered



C33-00082
燙鬥墊
iron pad

C17-RP-004-1M
3米原子喉連接頭x2條
3m Teflon hose with
fitting x 2 pcs

APT15-00068
布套
Cloth Sleeve

易損件 Wearings



C33-3702-8
蒸汽開關
Steam Valve

C33-3702-5
排水閥
Water Outlet Valve

C33-3700-3
熨鬥手柄
Iron Handle

型號 Model	蒸汽壓力(kgf/cm ²) Steam Pressure	蒸汽開關 Steam Valve	耗蒸汽量(kg/h) Steam Consumption	最高設計溫度(°C) Max. Designed Temp.	淨重(kg) Net Weight	熨鬥底尺寸(mm) Sole Size
NS-3703	3~5	手按式 Press handle type	5	135	1	190×60



藝誠(余氏)發展有限公司
Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下
G/F., 52 Wing Hong St.,

Cheung Sha Wan, Kln., Hong Kong.

Tel:(852)2741 9981, 2742 0078 E-MAIL:info@ngaishing.com
Fax:(852)2785 3149 Http://www.ngaishing.com