


NS-94AC-2/NS-94AC-2W

自動收料修筒車

Placket Cutting Machine with Automatic Stacker



1. 壓腳前設傍位，對準中線
Presser foot with center guide for center line positioning
2. 左右有吹風，吹去廢料
With left and right air blowing function to blow scraps away



3. 電眼感應自動收料，方便快捷
Photoelectric sensing for automatically materials stacking, convenient and quick

- 適用於襯衫前幅明筒對格、對中線及修筒，將前幅明筒按中線等邊切齊，方便前幅明筒車縫
- 採用伺服馬達運轉、高質鋼材製造切刀修筒，生產效率高、刀具使用壽命長
- 壓腳前設有可調節的傍位，方便對齊明筒中線
- 壓腳兩側設有吹風管，將修筒廢料自動吹掉
- 設有電眼感應自動收料系統，節省時間，提高工作效率
- 裁片裁切寬度可調，NS-94AC-2 出廠設定值為 $2\frac{1}{2}$ "，NS-94AC-2W 出廠設定值為4"

- Suitable for shirt front box placket plaid matching, central line aligning and placket trimming; shirt front box placket will be cut neatly and symmetrically to the central line, smoothing the way for subsequent sewing process
- Adopt servo motor for running, high quality of steel cutter for placket cutting, high production efficiency and long service life
- Adjustable guides are applied on front of the presser foot for easy aligning of the placket central line
- With air blowing pipes on both sides of the presser foot to remove scraps automatically
- Auto. material stacking by photoelectric sensing, so as to save time and improve efficiency
- Adjustable cut piece cutting width; NS-94AC-2 factory set value is $2\frac{1}{2}$ ", and NS-94AC-2W factory set value is 4"

型號 Model	電源 Power Supply	工作寬度(inch) Working Width	總功率(kW) Total Power	馬達轉速(RPM) Motor Speed	壓縮空氣壓力(kgf/cm ²) Compressed Air Pressure	毛重 (kg) Gross Weight	機身尺寸(mm) Machine Size	裝箱尺寸(mm) Packing Size
NS-94AC-2	1PH/220V/50Hz	$1\frac{1}{2} \sim 2\frac{3}{4}$	0.8	2200	5	165*	1080×670×1070	1230×1250×1070
NS-94AC-2W		$2\frac{3}{4} \sim 4$				167*		



藝誠(余氏)發展有限公司
Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下

G/F., 52 Wing Hong St.,

Cheung Sha Wan, Kln., Hong Kong.

Tel : (852) 2741 9981, 2742 0078

Fax : (852) 2785 3149

E-MAIL: info@ngaishing.com

Http://www.ngaishing.com